



LAPAROSCOPIC SURGERY

# AESCULAP® LED LIGHT SOURCE

# AESCULAP® LED LIGHT SOURCE







## Bright Light

Like a 300 W Xenon light source the LED light source provides high performance light suitable for any surgical intervention. The high color rendering index and the color temperature of approx. 5,700 K result in true-to-life colors.

### Daylight Quality

#### Reduced cost of ownership

The eco-friendly LED light source does not require frequent and expensive bulb replacements (compared to Xenon), is maintenance free and more economical due to the lower power consumption.

#### Efficiency

#### Increase patient safety

As much light as necessary, as little as possible. In combination with the Aesculap 2D/3D camera platform the LED light source automatically controls the light output dynamically to minimize the heat in the optical system.

### Built-in intelligence

#### For a better image

The integrated test unit provides information about the light transmission quality of the light cable. This helps to identify critical components that can lead to poor illumination and dark or noisy video images during endoscopic interventions.

#### Image quality

#### Quiet working environment

"Noise pollution" in the OR can be very annoying. The LED light source is almost inaudible.

#### Silence

Light Source	ltem no	Description
	OP950	LED Light Source

Accessories	ltem no.	Description
	OP941	Light cable adapter

Technical Specification		
System	LED module	
Light cable connector	AESCULAP®/Storz/Olympus/Wolf	
Manual light intensitiy control	Continuously via rotation knob (in steps of 5%)	
Automatic light control	Via camera control unit (MIS Bus)	
Display	2,4" monochrome display	
Color temperature	5,665 K (±6,3%)	
Light flux of LED module	2,510 lumen (± 3,6%)	
Anti glare protection	Built-in	
Light output measuring control	Integrated	
Maximum power consumption	240 W	
Dimensions (W x H x D)	330 x 146 x 362 mm	
Weight	8.5 kg	

# AESCULAP<sup>®</sup> – a B. Braun brand

Aesculap AG | Am Aesculap-Platz | 78532 Tuttlingen | Germany Phone +49 7461 95-0 | Fax +49 7461 95-2600 | www.aesculap.com

The main product trademark "Aesculap" is a registered trademark of Aesculap AG.

Subject to technical changes. All rights reserved. This brochure may only be used for the exclusive purpose of obtaining information about our products. Reproduction in any form partial or otherwise is not permitted.